



**Notes:**

Shown above are several methods for routing condensate hose and wick to outside of the enclosure. There may be other methods available. Choose a method that best fits your applications requirements.

INFORMATION DISCLOSED HEREIN IS THE CONFIDENTIAL PROPERTY OF TECA CORP. RECIPIENT SHALL NOT USE THE INFORMATION IN ANY UNAUTHORIZED MANNER.	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE:	<b>THERMOELECTRIC COOLING AMERICA CORP.</b>							
	<table border="1"> <tr> <td>DECIMALS</td> <td>ANGLE</td> </tr> <tr> <td>.XX +/-</td> <td>+/-</td> </tr> <tr> <td>.XXX +/-</td> <td>FRACTION +/-</td> </tr> </table>	DECIMALS	ANGLE	.XX +/-	+/-	.XXX +/-	FRACTION +/-	DVA-4200 DRIP PAN INSTALLATION	
DECIMALS	ANGLE								
.XX +/-	+/-								
.XXX +/-	FRACTION +/-								
FINISH:	MATERIAL:	DRAWN BY: AA	DRAWING # SK120823	REV LEVEL					
		DATE: 08/14/2012	SCALE	MASTER: SK120819					
REV	DESCRIPTION	Date	APPROVED	SHEET					
			D8505						