

AHP-3254

Air Conditioner/Heat Exchanger

Air Cooled Through Mounted Nema-12, 4, 4X 3 Phase, 208 VAC, 4 Wire Wye High Efficiency

2686 BTU/HR

FEATURES

- · High capacity thermoelectric design
- · Power saving air to air heat exchanger mode (ECO-Mode)
- · Heavy duty full perimeter mounting
- · Lower profile intrusion into enclosure
- · Central input cord for easy mounting
- · Closed loop design
- · Condensate control and evaporation system
- · Increased efficiency at higher ambients by as much as 10%
- · Virtually maintenance free
- · No compressor
- · Environmentaly friendly and safe
- · Stainless Steel exterior housing
- Mounts and operates in any orientation
- Integral temperature controller
- · Weight 88 LBS.

INCLUDES

- · Power supply
- · Temperature controller
- Power saving heat exchanger mode (ECO-Mode)
- Mounting gasket
- Mounting hardware
- · Power input cord
- Circuit breaker

1200	ACTIVE		
560100	ACI	IVE	
1000			
600			
600			
600			
400			
Commence of the commence of th	ECO		
200	200		
0			

CONTROL TEMPERATURES

35 °C
25 °C
10 °C
5 °C
0/+65 °C
0/+60 °C

POWER INPUTS

 Voltage, 3 Phase Wye
 208 VAC

 Current, Active (per phase)
 2.6 AMPS

 Current , ECO-Mode
 0.70 AMP

 Frequency
 50/60 Hz

PERFORMANCE RATINGS

 Cooling (Traditional)
 2686 BTU/HR

 Cooling (Din 3168)
 787 WATTS

 Cooling COP (at L35 L35)
 0.84

 Heating (Traditional)
 > 3294 BTU/HR

 Heating (Din 3168)
 > 937 WATTS


 Heating COP
 > 1.0

 Heat Exchanger (ECO-Mode)
 18 W/°C

CONFIGURATIONS					
MODEL	Part Number	NOTES	TEMPERATURE CONTROL	ENVIRONMENT	
AHP-3254	0-I4JE-0-000	Cool only, industrial fans & power supply	TC-4F	NEMA-12, IP 52	
AHP-3254	0-I45E-0-000	Cool only, industrial fans & power supply	EXT*	NEMA-12, IP 52	
AHP-3254HC	0-I4IE-1-000	Heat/Cool, industrial fans & power supply	TC-7F	NEMA-12, IP 52	
AHP-3254HC	0-I45E-1-000	Heat/Cool, industrial fans & power supply	EXT*	NEMA-12, IP 52	
AHP-3254XE	0-I4JE-4-000	Cool only, sealed hot side fans & power supply	TC-4F	NEMA-4/4X, IP 56	
AHP-3254XE	0-I45E-4-000	Cool only, sealed hot side fans & power supply	EXT*	NEMA-4/4X, IP 56	
AHP-3254XEHC	0-I4IE-5-000	Heat/Cool, sealed hot side fans & power supply	TC-7F	NEMA-4/4X, IP 56	
AHP-3254XEHC	0-I45E-5-000	Heat/Cool, sealed hot side fans & power supply	EXT*	NEMA-4/4X, IP 56	
AHP-3254X	0-I4JE-2-000	Cool only, Mil. grade hot side fans & power supply	TC-4F	NEMA-4X/Harsh, IP 56	
AHP-3254X	0-I45E-2-000	Cool only, Mil. grade hot side fans & power supply	EXT*	NEMA-4X/Harsh, IP 56	
AHP-3254XHC	0-I4IE-3-000	Heat/Cool, Mil. grade hot side fans & power supply	TC-7F	NEMA-4X/Harsh, IP 56	
AHP-3254XHC	0-I45E-3-000	Heat/Cool, Mil. grade hot side fans & power supply	EXT*	NEMA-4X/Harsh, IP 56	

^{*} Unit is set for 5-32 VDC external signal, relay(s) included

PERFORMANCE CURVE Cooling Capacity (BTU/HR) AHP-3254 MOUNTING STYLE



Equation of line: $y=\Delta T(^{\circ}C)$ x=Capacity (Watts)			
Enclosure Air	y=.041x-32.3		
Cold Sink	y=.030x-32.3		

MOUNTING STYLE Through Mounted ENVIRONMENTS SERVED NEMA-12 IP 52 NEMA-4,4X IP 56 RATING (TRADITIONAL) 2686 BTU/hr @ 0 °F ΔT 3610 BTU/hr @ +20 °F ΔT RATING (DIN 3168) 788 Watts L35 L35 420 Watts L35 L50

Air Flow Pattern

17.20X18.90 [437X480]

DIMENSIONS

