



AHP-6250

Air Cooled
Through Mounted
Nema-12, 4, 4X

Air Conditioner/Heat Exchanger

120 VAC Input
High Efficiency
4340 BTU/HR



FEATURES

- High capacity thermoelectric design
- Power saving air to air heat exchanger (ECO-mode)
- Heavy duty full perimeter mounting
- Lower profile intrusion into enclosure
- Central input cord for easy mounting
- Closed loop design
- Condensate control and evaporation system
- Increased efficiency at higher ambients by as much as 10%
- Virtually maintenance free
- No compressor
- Environmentally friendly and safe
- Stainless Steel exterior housing
- Mounts and operates in any orientation
- Integral temperature controller
- Weight 170 LBS.

CONTROL TEMPERATURES

Active Cooling	35 °C
Heat Exchanger (ECO-Mode)	25 °C
Active Heating	10 °C
Typical Hysteresis	5 °C
Operating Ambient	-40/+65 °C
Operating Enclosure	-10/+60 °C

POWER INPUTS


Voltage	120 VAC
Current, Active	14 AMPS
Current , ECO-Mode	3.0 AMP
Frequency	50/60 Hz

PERFORMANCE RATINGS

Cooling (Traditional)	4340 BTU/HR
Cooling (Din 3168)	1273 WATTS
Cooling COP (at L35 L35)	0.76
Heating (Traditional)	> 5524 BTU/HR
Heating (Din 3168)	> 1620 WATTS
Heating COP	> 1.0
Heat Exchanger (ECO-mode)	45 W/°C

INCLUDES

- Power supply
- Temperature controller
- Power saving heat exchanger mode (ECO-Mode)
- Mounting gasket
- Mounting hardware
- Power input cord
- Circuit breaker



250 VDC configuration for crane applications available

CONFIGURATIONS

MODEL	PART NUMBER	NOTES	TEMPERATURE CONTROL	ENVIRONMENT
AHP-6250	0-K4J0-0-000	Cool only, industrial fans & power supply	TC-4F	NEMA-12, IP 52
AHP-6250	0-K450-0-000	Cool only, industrial fans & power supply	EXT*	NEMA-12, IP 52
AHP-6250HC	0-K4I0-1-000	Heat/Cool, industrial fans & power supply	TC-7F	NEMA-12, IP 52
AHP-6250HC	0-K450-1-000	Heat/Cool, industrial fans & power supply	EXT*	NEMA-12, IP 52
AHP-6250XE	0-K4J0-4-000	Cool only, sealed hot side fans & power supply	TC-4F	NEMA-4/4X, IP 56
AHP-6250XE	0-K450-4-000	Cool only, sealed hot side fans & power supply	EXT*	NEMA-4/4X, IP 56
AHP-6250XEHC	0-K4I0-5-000	Heat/Cool, sealed hot side fans & power supply	TC-7F	NEMA-4/4X, IP 56
AHP-6250XEHC	0-K450-5-000	Heat/Cool, sealed hot side fans & power supply	EXT*	NEMA-4/4X, IP 56
AHP-6250X	0-K4J0-2-000	Cool only, Mil. grade hot side fans & power supply	TC-4F	NEMA-4X/Harsh, IP 56
AHP-6250X	0-K450-2-000	Cool only, Mil. grade hot side fans & power supply	EXT*	NEMA-4X/Harsh, IP 56
AHP-6250XHC	0-K4I0-3-000	Heat/Cool, Mil. grade hot side fans & power supply	TC-7F	NEMA-4X/Harsh, IP 56
AHP-6250XHC	0-K450-3-000	Heat/Cool, Mil. grade hot side fans & power supply	EXT*	NEMA-4X/Harsh, IP 56

* Unit is set for 5-32 VDC external signal, relay(s) included

AHP-6250**MOUNTING STYLE**

Through Mounted

ENVIRONMENTS SERVED

NEMA-12 IP 52

NEMA-4,4X IP 56

RATING (TRADITIONAL)



4340 BTU/hr @ 0 °F ΔT

6060 BTU/hr @ +20 °F ΔT


RATING (DIN 3168)

1273 Watts L35 L35

600 Watts L35 L50

Equation of line: $y = \Delta T(^{\circ}\text{C})$ $x = \text{Capacity (Watts)}$ Enclosure Air $y = .022x - 28$ Cold Sink $y = .016x - 28$ 

Air Flow Pattern

DIMENSIONS

Dimensions do not include hardware
 Mounting hardware and gasket included but not shown
 Dimension: Inches [Millimeters]