

FHP-3259

Air Conditioner/Heat Exchanger

Air Cooled
Flush Mounted
Nema-12, 4/4x

100-240 VAC Input
High Capacity
2200 BTU/HR



FEATURES

- High capacity thermoelectric design
- Power saving air to air heat exchanger mode (ECO-Mode)
- Heavy duty full perimeter mounting
- Lower profile intrusion into enclosure
- Central input cord for easy mounting
- Closed loop design
- Condensate control and evaporation system
- Compact
- Increased efficiency at higher ambient by as much as 10%
- Virtually maintenance free
- No compressor
- Environmentally friendly and safe
- Stainless Steel exterior housing
- Mounts and operates in any orientation
- Integral temperature controller
- Weight 90 LBS.

CONTROL TEMPERATURES

Active Cooling	35 °C
Heat Exchanger (ECO-Mode)	25 °C
Active Heating	10 °C
Typical Hysteresis	5 °C
Operating Ambient	-40/+65 °C
Operating Enclosure	-10/+60 °C

POWER INPUTS


Input Voltage	100 - 240 VAC
Current, Active	11 - 4.6 AMPS
Alternate Input Voltage	127 - 374 VDC
Current , ECO-Mode (@120 vac)	1.5 AMP
Frequency	47 - 63 / 440 Hz
Power Consumption	1100 Watts

PERFORMANCE RATINGS

Cooling (Traditional)	2200 BTU/HR
Cooling (Din 3168)	650 WATTS
Cooling COP (at L35 L35)	0.56
Heating (Traditional)	> 1200 BTU/HR
Heating (Din 3168)	> 352 WATTS
Heating COP	> 1.0
Heat Exchanger (ECO-Mode)	12.5 W/°C

INCLUDES

- Power supply
- Temperature controller
- Power saving heat exchanger mode (ECO-Mode)
- Mounting gasket
- Mounting hardware
- Power input cord



200 - 277 VAC (254 - 420 VDC) Versions available

CONFIGURATIONS

MODEL	PART NUMBER	NOTES	TEMPERATURE CONTROL	ENVIRONMENT
FHP-3259	7-I5JB-0-000	Cool only, industrial fans	TC-4F	NEMA-12, IP 52
FHP-3259	7-I55B-0-000	Cool only, industrial fans	EXT*	NEMA-12, IP 52
FHP-3259HC	7-I5IB-1-000	Heat/Cool, industrial fans	TC-7F	NEMA-12, IP 52
FHP-3259HC	7-I55B-1-000	Heat/Cool, industrial fans	EXT*	NEMA-12, IP 52
FHP-3259XE	7-I5JB-4-000	Cool only, sealed hot side fans	TC-4F	NEMA-4/4X, IP 56
FHP-3259XE	7-I55B-4-000	Cool only, sealed hot side fans	EXT*	NEMA-4/4X, IP 56
FHP-3259XEHC	7-I5IB-5-000	Heat/Cool, sealed hot side fans	TC-7F	NEMA-4/4X, IP 56
FHP-3259XEHC	7-I55B-5-000	Heat/Cool, sealed hot side fans	EXT*	NEMA-4/4X, IP 56
FHP-3259XEHC†	7-I5LB-5-000	Heat/Cool, sealed hot side fans	TC-5300D	NEMA-4/4X, IP56
FHP-3259HC†	7-I5LB-1-000	Heat/Cool, industrial fans	TC-5300D	NEMA-12, IP 52

† Precise temperature control model

* Unit is set for 5-32 VDC external signal, relay(s) included

TECA

1-888-TECA-USA (832-2872)

www.thermoelectric.com

FHP-3259**MOUNTING STYLE**

Flush Mounted

ENVIRONMENTS SERVED

NEMA-12 IP 52

NEMA-4/4X IP 56


RATING (TRADITIONAL)

2200 BTU/hr @ 0 °F ΔT


RATING (DIN 3168)

650 Watts L35 L35

325 Watts L35 L50



Equation of line: $y = \Delta T(^{\circ}\text{C})$ $x = \text{Capacity (Watts)}$		
Ambient Temp	35°C	50°C
Enclosure Air	$y = .043x - 27.8$	$y = .043x - 29$
Cold Sink	$y = .032x - 27.8$	$y = .032x - 29$



Air Flow Pattern

DIMENSIONS