

FHP-6252

Air Conditioner/Heat Exchanger

Air Cooled
Flush Mounted
Nema-12, 4, 4X

240 VAC Input
High Capacity
4480 BTU/HR

FEATURES

- High capacity thermoelectric design
- Power saving air to air heat exchanger (ECO-mode)
- Heavy duty full perimeter mounting
- No intrusion into enclosure
- Central input cord for easy mounting
- Closed loop design
- Condensate control and evaporation system
- Increased efficiency at higher ambients by as much as 10%
- Virtually maintenance free
- No compressor
- Environmentally friendly and safe
- Stainless Steel exterior housing
- Mounts and operates in any orientation
- Integral temperature controller
- Weight 180 LBS.



CONTROL TEMPERATURES

Active Cooling	35 °C
Heat Exchanger (ECO-Mode)	25 °C
Active Heating	10 °C
Typical Hysteresis	5 °C
Operating Ambient	-40/+65 °C
Operating Enclosure	-10/+60 °C

POWER INPUTS


Voltage	240 VAC
Current, Active	9.2 AMPS
Current, ECO-Mode	1.5 AMP
Frequency	50/60 Hz

PERFORMANCE RATINGS

Cooling (Traditional)	4480 BTU/HR
Cooling (Din 3168)	1315 WATTS
Cooling COP (at L35 L35)	0.60
Heating (Traditional)	> 7365 BTU/HR
Heating (Din 3168)	> 2160 WATTS
Heating COP	> 1.0
Heat Exchanger (ECO-mode)	45 W/°C

INCLUDES

- Power supply
- Temperature controller
- Power saving heat exchanger mode (ECO-Mode)
- Mounting gasket
- Mounting hardware
- Power input cord
- Circuit breaker



250 VDC configuration for crane applications available


CONFIGURATIONS

MODEL	PART NUMBER	NOTES	TEMPERATURE CONTROL	ENVIRONMENT
FHP-6252	7-K4J2-0-000	Cool only, industrial fans & power supply	TC-4F	NEMA-12, IP 52
FHP-6252	7-K452-0-000	Cool only, industrial fans & power supply	EXT*	NEMA-12, IP 52
FHP-6252HC	7-K4I2-1-000	Heat/Cool, industrial fans & power supply	TC-7F	NEMA-12, IP 52
FHP-6252HC	7-K452-1-000	Heat/Cool, industrial fans & power supply	EXT*	NEMA-12, IP 52
FHP-6252XE	7-K4J2-4-000	Cool only, sealed hot side fans & power supply	TC-4F	NEMA-4, IP 56
FHP-6252XE	7-K452-4-000	Cool only, sealed hot side fans & power supply	EXT*	NEMA-4, IP 56
FHP-6252XEHC	7-K4I2-5-000	Heat/Cool, sealed hot side fans & power supply	TC-7F	NEMA-4, IP 56
FHP-6252XEHC	7-K452-5-000	Heat/Cool, sealed hot side fans & power supply	EXT*	NEMA-4, IP 56
FHP-6252X	7-K4J2-2-000	Cool only, Mil. grade hot side fans & power supply	TC-4F	NEMA-4X, IP 56
FHP-6252X	7-K452-2-000	Cool only, Mil. grade hot side fans & power supply	EXT*	NEMA-4X, IP 56
FHP-6252XHC	7-K4I2-3-000	Heat/Cool, Mil. grade hot side fans & power supply	TC-7F	NEMA-4X, IP 56
FHP-6252XHC	7-K452-3-000	Heat/Cool, Mil. grade hot side fans & power supply	EXT*	NEMA-4X, IP 56

* Unit is set for 5-32 VDC external signal, relay(s) included

FHP-6252

PERFORMANCE CURVE



Equation of line: $y = \Delta T(^{\circ}C)$ $x = \text{Capacity (Watts)}$		
Ambient	35 C	50 C
Enclosure Air	$y = -.023x - 30.2$	$y = -.023x - 30.8$
Cold Sink	$y = -.016x - 30.2$	$y = -.016x - 30.8$

MOUNTING STYLE

Flush Mounted

ENVIRONMENTS SERVED

NEMA-12 IP 52

NEMA-4,4X IP 56

RATING (TRADITIONAL)


4480 BTU/hr @ 0 °F ΔT

6125 BTU/hr @ +20 °F ΔT

RATING (DIN 3168)

1315 Watts L35 L35

687 Watts L35 L50



Air Flow Pattern

DIMENSIONS

